

# **GS11UV** Technical Data Sheet

### **Description and Applications**

Tenopex<sup>®</sup> GS11UV is an extruded polished / polished clear polycarbonate film with the capability of absorbing UV wave at 380nm, comprising excellent mechanical and optical properties. Besides, it offers excellent transparency, high temperature resistance, good dimensional stability with ease of secondary processing. These films are recommended for the outdoor usages such as outdoor nameplates and sign boards, or screens or decoration parts of the equipments or environments which produce or under exposure of UV waves.

## **Typical Property Values**

Property	Test Method	Units	Value
Physical			
Density	ASTM D792	g/cm <sup>3</sup>	1.2
Water Absorption , 24hrs	ASTM D570	%	0.4
Optical			
Light Transmission	ASTM D1003	%	89-91
Haze	ASTM D1003	%	0.4
Mechanical			
Tensile Strength	ASTM D882	MPa	≥60
Tensile Elongation at Break	ASTM D882	%	100-150
Young Modulus	ASTM D882	MPa	≥2100
Impact Strength (0.76mm)	ISO 6603-1	J	31
Thermal			
Heat Deflection Temperature at 1.82Mpa	ASTM D648	°C	135
Coefficient of Thermal Expansion	ASTM D696	10 <sup>-5</sup> /°C	7
Coefficient of Thermal Exchange	ASTM C177	W/m.°C	0.19

Tenopex Plastics Co., Ltd



## **GS11UV** Technical Data Sheet

Electrical				
Dielectric Strength	ASTM D149	V	17000	
Surface Resistivity	ASTM D257	Ω/square	10 <sup>15</sup>	
Volume Resistivity	ASTM D257	Ω.cm	10 <sup>16</sup>	
UL Flammability				
<b>UL Flammability</b> Film thickness <sub>≤ 0.25</sub> mm	UL94		VTM-2	

### **Manufacturing Gauge Specifications**

	Min/Max Tolerances
Nominal Gauge Ranges	of Nominal
0.5mm - 1.0mm	+/- 5%

These are typical properties and are not intended for specification purposes. If minimum certifiable properties are required, please contact your local sales representative. Reported values are based on 0.500 mm thickness film unless otherwise noted. Each user is responsible for making its own determination as to the suitability of Tenopex's products, services and recommendations for the user's particular use through appropriate end-use testing and analysis. Although any information or technical recommendation will be given without warranty nor guarantee nor implied, that the results indicated herein are obtained under end-use conditions. Except as provided in seller's standard conditions of sale, seller shall not be responsible for any loss resulting from any uses of its products or services described herein.

Tenopex Plastics Co., Ltd

No 3, KeYuan 5th Road, TangXia Town, Dongguan City, GuangDong Province, China 523718 Website : www.tenopexplastics.com E-mail : marketing@tenopex.com